

25, 40 And 50 A panel SSR, "hockey puck" style

- "hockey puck" housing with cover
- 24 to 240 V AC output
- Zero-crossing version
- High switching speed
- High endurance
- Silent switching
- Spark and bounce-free switching
- Low control power
- 3-phase general purpose
- "Relay-style" terminal arrangement (input and output terminals on opposite sides)
- Mounting on heatsink with screws

77.x5
Screw terminal (plate clamp)



* See L77-11 diagrams page 13
** See L77-8, L77-9 and L77-10 diagrams page 13


For outline drawing see page 16

77.25.x.xxx.8250



Zero-crossing switch-on

- Output: 25 A/230 V AC
- Suggested applications: heater control




Simplified circuit diagram

77.45.x.xxx.8250



Zero-crossing switch-on

- Output: 40 A/230 V AC
- Suggested applications: heater control




Simplified circuit diagram

77.55.x.xxx.8250



Zero-crossing switch-on

- Output: 50 A/230 V AC
- Suggested applications: heater control



Simplified circuit diagram

Output specification

Output configuration		1 NO (SPST-NO)	1 NO (SPST-NO)	1 NO (SPST-NO)
Rated current I_N /Max. peak current* (10 ms) A		25/300*	40/500*	50/520*
Rated voltage V AC (50/60 Hz)		230	230	230
Switching voltage range V AC (50/60 Hz)		21.6...280	21.6...280	21.6...280
Repetitive peak off-state voltage V_{pk}		600	600	600
Nominal lamp rating:				
230 V incandescent/halogen W		2000	4000	6000
fluorescent tubes with electronic ballast W		2000	4000	6000
fluorescent tubes with electromechanical ballast W		1000	2000	3000
CFL W		800	3000	4000
230 V LED W		800	3000	4000
LV halogen or LED with electronic ballast W		800	3000	4000
LV halogen or LED with electromechanical ballast W		1000	3000	4000
Minimum switching current @ 250 V mA		120	250	250
Typical "OFF-state" leakage current @ 250 V mA		10	10	10
Max "ON-state" voltage drop @ 25 °C and I_N V		1.6	1.6	1.6
Power loss @ I_N W		40	64	80

Input specification

Nominal voltage (U_N)	V AC (50/60 Hz)	—	230	—	230	—	230
	V DC	24	—	24	—	24	—
Rated power @ U_{MAX}	VA (50 Hz)/W	—/0.6	2.4/—	—/0.6	2.4/—	—/0.6	2.4/—
Operating range	V AC (50/60 Hz)	—	90...280	—	90...280	—	90...280
	V DC	3...32	—	3...32	—	3...32	—
Must drop-out voltage	V AC (50/60 Hz)/DC	—/1	10/—	—/1	10/—	—/1	10/—

Technical data

Electrical life	cycles	10 · 10 ⁶		10 · 10 ⁶		10 · 10 ⁶	
Operate/release time	ms	10/10	40/80	10/10	40/80	10/10	40/80
Insulation between input and output (1.2/50 μs)	kV	5.6		5.6		5.6	
Ambient temperature	°C	-30...+80**		-30...+80**		-30...+80**	
Protection category		IP 20		IP 20		IP 20	

Approvals (according to type)

