



*** SPARE PART*** SIMATIC S7-1200,
COMMUNICATION COMMUNICATION MODULE CM 1241,
RS232, 9 PIN SUB D (MALE),
SUPPORTS MESSAGE BASED FREEPORT

| | |
|---|---|
| Input current | |
| Current consumption, max. | 220 mA ; From L5+; logic |
| Power losses | |
| Power loss, typ. | 1.1 W |
| Interfaces | |
| Number of interfaces | 1 |
| Interface physics, RS 232C (V.24) | Yes |
| Point-to-point | |
| Cable length, max. | 10 m |
| Integrated protocol driver | |
| ASCII | Yes |
| Climatic and mechanical conditions for storage and transport | |
| Climatic conditions for storage and transport | |
| Free fall | |
| Drop height, max. (in packaging) | 0.3 m ; five times, in dispatch package |
| Relative humidity | |
| Permissible range (without condensation) at 25 °C | 95 % |
| Mechanical and climatic conditions during operation | |

| | |
|---|--|
| Climatic conditions in operation | |
| Temperature | |
| Permissible temperature range | 0 °C to 55 °C horizontal installation, 0 °C to 45 °C vertical installation |
| Software | |
| Runtime software | |
| Target system | |
| S7-1200 | Yes |
| Dimensions | |
| Width | 30 mm |
| Height | 100 mm |
| Depth | 75 mm |
| Weights | |
| Weight, approx. | 150 g |
| Status | Dec 11, 2014 |